

PRODUCT INFORMATION



Lubricants - Engine Oil - Passenger Car Motor Oils

Valvoline™ SynPower™ DT C2 0W-30

Premium quality synthetic motor oil. Formulated for ultimate performance and protection under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

OEM Approvals

Jaguar Landrover STJLR.03.5007

Performance Levels

ACEA C2

API SP

Fiat 9.55535-GS1, -DS1

VWC 53035

Recommended for in-warranty service fill where Ford WSS-M2C950-A is required

Recommended by Valvoline for use where Iveco 1811 SC1 LV-16 is required

Suitable for use in some models of*:
Honda, Jeep, Mitsubishi, Subaru, Suzuki, Toyota

* Please consult owner's manual before use

Applications

Formulated for Euro 5 and 6 diesel engines equipped with DPF technology (diesel particulate filter), and/or TWC (three-way catalyst). Also suitable for petrol and LPG engines.

Specially formulated for use in Ford Duratorq TDCI Euro 5 and 6 engines.

Features & Benefits

Ultimate protection and performance

SynPower engine oil is formulated with the highest quality base oils and latest additives to ensure ultimate protection and performance under all operating conditions. Designed to fulfill the latest standards of leading engine manufacturers.

Engine cleanliness

Keeps engine extremely clean by minimizing deposits.

Fuel Economy

Low viscosity and special additives result in maximum reduction of friction which results in a lower fuel consumption. Demonstrates up to 0.7% fuel economy improvement in relation to higher viscosity reference fluids (SAE 5W-30 to WSS M2C913 D).

Optimized for emission control systems

Specifically designed for use with emission control systems like DPF (Diesel Particulate Filter) and TWC (Three Way Catalyst) systems. Low SAPS output keeps the emission control system clean and in optimal conditions.

Excellent cold start performance

Instant oil flow at low temperatures provides easy cold starts and optimal lubrication within seconds after ignition.

Long drain interval

Formulated for excellent product stability. Long lasting performance and suitable for long drain intervals.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants, transmission fluids, gear oils, hydraulic lubricants, automotive chemicals, specialty products, greases, and cooling system products.

For more information on Valvoline products, programs and services please visit <https://www.valvolineglobal.com/en-eur/> or <http://pisheets.valvolineglobal.com>

Health & Safety

For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at <http://sds.valvolineglobal.com>

Typical properties

SynPower DT C2	
SAE Viscosity Grade	0W-30
Viscosity @ 100°C, mm²/s ASTM D445	9.7
Viscosity @ 40°C, mm²/s ASTM D445	46
Viscosity Index ASTM D2270	203
Viscosity @ -35°C, mPa.s ASTM D5293	< 6000
TBN, mg KOH/g ASTM D2896	8.0
Pour Point, °C ASTM D5949	-45
Density @ 15°C, g/cm³ ASTM D4052	0.845
Flash Point, COC, °C ASTM D92	224

*The data provided is for reference only and can be applied only for the specific production location

This information only applies to products manufactured in the following location(s): Europe

Effective date: 5/19/2026